

WING BOOST 3

addressable LED lighting



Wing Boost 3 RGB Triple version offers tremendous power and lots of stylish lighting effects.

120mm ARGB PWM fans

With 16.8 million colors, the Wing Boost 3 RGB offers many possibilities to make your case shine uniquely. The addressable RGB LED lighting is integrated in the frame and casts a slight glow on the impeller and radiates outwards in style.



Wing Boosts

Thanks to the Wing Boost 3 technology, air turbulence at the impeller is greatly reduced to ensure even quieter operation at full fan speed.

Compatibility





Fan specifications

Dimensions:	120 x 120 x 25 mm
Speed:	500 - 1600 rpm
Bearing:	Hydraulic Bearing
Rated Voltage:	12 VDC
Airflow:	92,6 m ³ /h
Noise level:	23,5 dB(A)
Pressure:	2,19 mm H ₂ O
Connection:	4-Pin PWM / 3-Pin ARGB

De-vibration rubber

The de-vibration rubbers reduce the often annoying noises, which are transmitted by the vibrations of the fan to the case, by their excellent anti-vibration characteristics to a minimum.



Blade geometry

Wing Boost 3 RGB has an optimized asymmetrical blade geometry for favored axial flow alignment. Prevention of the actual flow direction at increased backpressure.



Accessories

Triple version

- 1x RF Remote Controller
- 1x RF Receiver
- 12x Radiator screw
- 12x Case Screw
- 1x RGB Splitter
- 1x PWM Splitter



Press this button to turn on/off LED lighting.



Press these 2 buttons to change the lighting mode.



Press these 2 buttons to change the lighting speed.



Press these 2 buttons to change the lighting brightness.



This button enables the lighting into AUTO/Display mode.



This button is for controller/receiver match function.



This button is for setting function.



Choose single static color with these 4 buttons.

